



High Efficiency **Downdraft Table**

Advanced state-of-the-art design delivers high air volume, low-pressure drop with primary and secondary filtration as standard equipment.

Our filters are arranged vertically for better release and performance, the only manufacturer that offers these two key features!

These tables are suitable for wood sanding, metal dust, grinding, and welding applications.

Call today to discuss your application.

Standard Features:

- Infinitely Variable Volume: Zero to 4800 AFM
 - Downdraft Velocity: 200 ft. per minute, Actual
 - Air Volume: 4800 ACFM* @ 3" static pressure
 - Sound Level: 75 dB (A) @ 5 ft.
 - Automatic, Pulse-Jet Filter Cleaning
 - Primary Filtration: Nanofiber 99.999% @ 0.5 Micron
 - 4 Filters @ 117 sq. ft. / 468 sq. ft. Total Filter Area
 - Secondary Filtration: Multi-Pleat 80% @ 9.0 Micron
 - 3 Filters @ 19.6 sq. ft. / 58.8 sq. ft. Total Filter Area
 - Work Surface Area: 48" x 72" / 24 sq. ft.
 - Power Requirements: 5.33 BHP / 7.5 HP TEFC
 - 208/230/460/575/60/3
 - Dimensions: 48" W x 72" L x 34" H
 - Weight: 600 lbs.
 - Differential Pressure Gauge
- *ACFM = Actual Cubic Feet per Minute

Options:

- 3-Sided Spark Shield
- Backdraft/Downdraft
- Canopy Hood
- Capture Arm
- Casters
- Class II, Div II Electrics
- Ergonomic Foot Rest
- HEPA / Carbon Filtration
- Light Bars
- Non-Ferrous Metal Package
- Table Top Options:
Wood/Rubber/Plastic/
Fiberglass/Steel

Contact Information

Air Dynamics Industrial Systems Corporation

180 Roosevelt Ave. York, PA. 17401 U.S.A

P • 717-854-4050

sales@airdynamics.net

www.airdynamics.net

Call our technicians to discuss your challenge today!